

Inventory Control Form

RFN-ADVANCED™

Retrograde Femoral Nailing System

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 844-243-4321

Date: _____



Hospital: _____

Surgeon: _____



Procedure: _____

Implants



RFN-ADVANCED™ System Ø 9 mm Diameter Nail, Sterile

Standard Bend	Periprosthetic Bend	Length (mm)	
<input type="checkbox"/> 04.233.916S	<input type="checkbox"/> 04.233.917S	160 mm	 Standard Bend  Periprosthetic Bend
<input type="checkbox"/> 04.233.920S	<input type="checkbox"/> 04.233.921S	200 mm	
<input type="checkbox"/> 04.233.924S	<input type="checkbox"/> 04.233.925S	240 mm	
<input type="checkbox"/> 04.233.928S	<input type="checkbox"/> 04.233.929S	280 mm	
<input type="checkbox"/> 04.233.930S	<input type="checkbox"/> 04.233.931S	300 mm	
<input type="checkbox"/> 04.233.932S	<input type="checkbox"/> 04.233.933S	320 mm	
<input type="checkbox"/> 04.233.934S	<input type="checkbox"/> 04.233.935S	340 mm	
<input type="checkbox"/> 04.233.936S	<input type="checkbox"/> 04.233.937S	360 mm	
<input type="checkbox"/> 04.233.938S	<input type="checkbox"/> 04.233.939S	380 mm	
<input type="checkbox"/> 04.233.940S	<input type="checkbox"/> 04.233.941S	400 mm	
<input type="checkbox"/> 04.233.942S	<input type="checkbox"/> 04.233.943S	420 mm	
<input type="checkbox"/> 04.233.944S	<input type="checkbox"/> 04.233.945S	440 mm	
<input type="checkbox"/> 04.233.946S	<input type="checkbox"/> 04.233.947S	460 mm	
<input type="checkbox"/> 04.233.948S	<input type="checkbox"/> 04.233.949S	480 mm	



RFN-ADVANCED™ System Ø 10 mm Diameter Nail, Sterile

Standard Bend	Periprosthetic Bend	Length (mm)	
<input type="checkbox"/> 04.233.016S	<input type="checkbox"/> 04.233.017S	160 mm	 Standard Bend  Periprosthetic Bend
<input type="checkbox"/> 04.233.020S	<input type="checkbox"/> 04.233.021S	200 mm	
<input type="checkbox"/> 04.233.024S	<input type="checkbox"/> 04.233.025S	240 mm	
<input type="checkbox"/> 04.233.028S	<input type="checkbox"/> 04.233.029S	280 mm	
<input type="checkbox"/> 04.233.030S	<input type="checkbox"/> 04.233.031S	300 mm	
<input type="checkbox"/> 04.233.032S	<input type="checkbox"/> 04.233.033S	320 mm	
<input type="checkbox"/> 04.233.034S	<input type="checkbox"/> 04.233.035S	340 mm	
<input type="checkbox"/> 04.233.036S	<input type="checkbox"/> 04.233.037S	360 mm	
<input type="checkbox"/> 04.233.038S	<input type="checkbox"/> 04.233.039S	380 mm	
<input type="checkbox"/> 04.233.040S	<input type="checkbox"/> 04.233.041S	400 mm	
<input type="checkbox"/> 04.233.042S	<input type="checkbox"/> 04.233.043S	420 mm	
<input type="checkbox"/> 04.233.044S	<input type="checkbox"/> 04.233.045S	440 mm	
<input type="checkbox"/> 04.233.046S	<input type="checkbox"/> 04.233.047S	460 mm	
<input type="checkbox"/> 04.233.048S	<input type="checkbox"/> 04.233.049S	480 mm	

RFN-ADVANCED™ System Ø 11 mm Diameter Nail, Sterile

Standard Bend	Periprosthetic Bend	Length (mm)	
<input type="checkbox"/> 04.233.116S	<input type="checkbox"/> 04.233.117S	160 mm	 Standard Bend  Periprosthetic Bend
<input type="checkbox"/> 04.233.120S	<input type="checkbox"/> 04.233.121S	200 mm	
<input type="checkbox"/> 04.233.124S	<input type="checkbox"/> 04.233.125S	240 mm	
<input type="checkbox"/> 04.233.128S	<input type="checkbox"/> 04.233.129S	280 mm	
<input type="checkbox"/> 04.233.130S	<input type="checkbox"/> 04.233.131S	300 mm	
<input type="checkbox"/> 04.233.132S	<input type="checkbox"/> 04.233.133S	320 mm	
<input type="checkbox"/> 04.233.134S	<input type="checkbox"/> 04.233.135S	340 mm	
<input type="checkbox"/> 04.233.136S	<input type="checkbox"/> 04.233.137S	360 mm	
<input type="checkbox"/> 04.233.138S	<input type="checkbox"/> 04.233.139S	380 mm	
<input type="checkbox"/> 04.233.140S	<input type="checkbox"/> 04.233.141S	400 mm	
<input type="checkbox"/> 04.233.142S	<input type="checkbox"/> 04.233.143S	420 mm	
<input type="checkbox"/> 04.233.144S	<input type="checkbox"/> 04.233.145S	440 mm	
<input type="checkbox"/> 04.233.146S	<input type="checkbox"/> 04.233.147S	460 mm	
<input type="checkbox"/> 04.233.148S	<input type="checkbox"/> 04.233.149S	480 mm	

RFN-ADVANCED™ System Ø 12 mm Diameter Nail, Sterile

Standard Bend	Periprosthetic Bend	Length (mm)	
<input type="checkbox"/> 04.233.216S	<input type="checkbox"/> 04.233.217S	160 mm	 Standard Bend  Periprosthetic Bend
<input type="checkbox"/> 04.233.220S	<input type="checkbox"/> 04.233.221S	200 mm	
<input type="checkbox"/> 04.233.224S	<input type="checkbox"/> 04.233.225S	240 mm	
<input type="checkbox"/> 04.233.228S	<input type="checkbox"/> 04.233.229S	280 mm	
<input type="checkbox"/> 04.233.230S	<input type="checkbox"/> 04.233.231S	300 mm	
<input type="checkbox"/> 04.233.232S	<input type="checkbox"/> 04.233.233S	320 mm	
<input type="checkbox"/> 04.233.234S	<input type="checkbox"/> 04.233.235S	340 mm	
<input type="checkbox"/> 04.233.236S	<input type="checkbox"/> 04.233.237S	360 mm	
<input type="checkbox"/> 04.233.238S	<input type="checkbox"/> 04.233.239S	380 mm	
<input type="checkbox"/> 04.233.240S	<input type="checkbox"/> 04.233.241S	400 mm	
<input type="checkbox"/> 04.233.242S	<input type="checkbox"/> 04.233.243S	420 mm	
<input type="checkbox"/> 04.233.244S	<input type="checkbox"/> 04.233.245S	440 mm	
<input type="checkbox"/> 04.233.246S	<input type="checkbox"/> 04.233.247S	460 mm	
<input type="checkbox"/> 04.233.248S	<input type="checkbox"/> 04.233.249S	480 mm	

Inventory Control Form

RFN-ADVANCED™

Retrograde Femoral Nailing System

Implants (continued)

*Available non-sterile and sterile packed. Add "TS" to catalog number to order Sterile Tube product.
Add "S" to catalog number to order standard sterile product.

RFN-ADVANCED™ System Ø 14 mm Diameter Nail, Sterile



	Standard Bend	Length (mm)
<input type="checkbox"/>	04.233.428S	280 mm
<input type="checkbox"/>	04.233.430S	300 mm
<input type="checkbox"/>	04.233.432S	320 mm
<input type="checkbox"/>	04.233.434S	340 mm
<input type="checkbox"/>	04.233.436S	360 mm
<input type="checkbox"/>	04.233.438S	380 mm
<input type="checkbox"/>	04.233.440S	400mm
<input type="checkbox"/>	04.233.442S	420 mm
<input type="checkbox"/>	04.233.444S	440 mm
<input type="checkbox"/>	04.233.446S	460 mm
<input type="checkbox"/>	04.233.448S	480 mm

End Caps, for RFNA, Sterile

Part #	Extension (mm)
<input type="checkbox"/>	04.233.000S 0 mm
<input type="checkbox"/>	04.233.005S 5 mm
<input type="checkbox"/>	04.233.010S 10 mm



Nuts and Washers, Sterile

Part #	Description
<input type="checkbox"/>	04.045.780S Washer for Screw Ø 14/7 mm
<input type="checkbox"/>	04.045.781S Nut Ø 14 mm
<input type="checkbox"/>	04.045.782S Washer for Nut Ø 17.5/11.8 mm



5 mm Locking Screws for IM Nails with XL25 recess



Locking Screws	Low Profile Locking Screws	Length (mm)
<input type="checkbox"/>	04.045.026*	26 mm
<input type="checkbox"/>	04.045.028*	28 mm
<input type="checkbox"/>	04.045.030*	30 mm
<input type="checkbox"/>	04.045.032*	32 mm
<input type="checkbox"/>	04.045.034*	34 mm
<input type="checkbox"/>	04.045.036*	36 mm
<input type="checkbox"/>	04.045.038*	38 mm
<input type="checkbox"/>	04.045.040*	40 mm
<input type="checkbox"/>	04.045.042*	42 mm
<input type="checkbox"/>	04.045.044*	44 mm
<input type="checkbox"/>	04.045.046*	46 mm
<input type="checkbox"/>	04.045.048*	48 mm
<input type="checkbox"/>	04.045.050*	50 mm
<input type="checkbox"/>	04.045.052*	52 mm
<input type="checkbox"/>	04.045.054*	54 mm
<input type="checkbox"/>	04.045.056*	56 mm
<input type="checkbox"/>	04.045.058*	58 mm
<input type="checkbox"/>	04.045.060*	60 mm
<input type="checkbox"/>	04.045.062*	62 mm
<input type="checkbox"/>	04.045.064*	64 mm
<input type="checkbox"/>	04.045.066*	66 mm
<input type="checkbox"/>	04.045.068*	68 mm
<input type="checkbox"/>	04.045.070*	70 mm
<input type="checkbox"/>	04.045.072*	72 mm
<input type="checkbox"/>	04.045.074*	74 mm
<input type="checkbox"/>	04.045.076*	76 mm
<input type="checkbox"/>	04.045.078*	78 mm
<input type="checkbox"/>	04.045.080*	80 mm
<input type="checkbox"/>	04.045.082*	82 mm
<input type="checkbox"/>	04.045.084*	84 mm
<input type="checkbox"/>	04.045.086*	86 mm
<input type="checkbox"/>	04.045.088*	88 mm
<input type="checkbox"/>	04.045.090*	90 mm
<input type="checkbox"/>	04.045.095*	95 mm
<input type="checkbox"/>	04.045.100*	100 mm
<input type="checkbox"/>	04.045.105*	105 mm
<input type="checkbox"/>	04.045.110*	110 mm
<input type="checkbox"/>	04.045.115*	115 mm
<input type="checkbox"/>	04.045.120*	120 mm

Inventory Control Form

RFN-ADVANCED™

Retrograde Femoral Nailing System

Implants (continued)

◊ Available non-sterile and sterile packed. Add "TS" to catalog number to order Sterile Tube product.

* Available sterile packed only. Add "S" to catalog number to order sterile blister-packed product. Add "TS" to catalog number to order Sterile tube product.

RFN-ADVANCED™ System

Locking Attachment Washer (LAW), Sterile

Part #			
<input type="checkbox"/> 02.233.100S	5°	Right	
<input type="checkbox"/> 02.233.101S	5°	Left	
<input type="checkbox"/> 02.233.104S	10°	Right	
<input type="checkbox"/> 02.233.105S	10°	Left	



Drill Bit

Part #	
<input type="checkbox"/> 03.133.108	Ø 2.8 mm Drill Bit, 110 mm Calibration, QC
<input type="checkbox"/> 03.133.108S	Ø 2.8 mm Drill Bit, 110 mm Calibration, QC, Sterile



Locking Screws for use with Locking Attachment Washer



OPTILINK™ 5.0 mm VA° Locking Screws

Part #	Length (mm)
<input type="checkbox"/> 42.231.214	14 mm
<input type="checkbox"/> 42.231.216	16 mm
<input type="checkbox"/> 42.231.218	18 mm
<input type="checkbox"/> 42.231.220	20 mm
<input type="checkbox"/> 42.231.222	22 mm
<input type="checkbox"/> 42.231.224	24 mm
<input type="checkbox"/> 42.231.226	26 mm
<input type="checkbox"/> 42.231.228	28 mm
<input type="checkbox"/> 42.231.230	30 mm
<input type="checkbox"/> 42.231.232	32 mm
<input type="checkbox"/> 42.231.234	34 mm
<input type="checkbox"/> 42.231.236	36 mm
<input type="checkbox"/> 42.231.238	38 mm
<input type="checkbox"/> 42.231.240	40 mm
<input type="checkbox"/> 42.231.242	42 mm
<input type="checkbox"/> 42.231.244	44 mm
<input type="checkbox"/> 42.231.246	46 mm
<input type="checkbox"/> 42.231.248	48 mm
<input type="checkbox"/> 42.231.250	50 mm
<input type="checkbox"/> 42.231.255	55 mm
<input type="checkbox"/> 42.231.260	60 mm
<input type="checkbox"/> 42.231.265	65 mm
<input type="checkbox"/> 42.231.270	70 mm
<input type="checkbox"/> 42.231.275	75 mm
<input type="checkbox"/> 42.231.280	80 mm
<input type="checkbox"/> 42.231.285	85 mm
<input type="checkbox"/> 42.231.290	90 mm
<input type="checkbox"/> 42.231.295*	95 mm
<input type="checkbox"/> 42.231.300*	100 mm
<input type="checkbox"/> 42.231.305*	105 mm



3.5 mm Variable Angle° Locking Screws

Part #	Length (mm)
<input type="checkbox"/> 02.127.114	14 mm
<input type="checkbox"/> 02.127.116	16 mm
<input type="checkbox"/> 02.127.118	18 mm
<input type="checkbox"/> 02.127.120	20 mm
<input type="checkbox"/> 02.127.122	22 mm
<input type="checkbox"/> 02.127.124	24 mm
<input type="checkbox"/> 02.127.126	26 mm
<input type="checkbox"/> 02.127.128	28 mm
<input type="checkbox"/> 02.127.130	30 mm
<input type="checkbox"/> 02.127.132	32 mm
<input type="checkbox"/> 02.127.134	34 mm
<input type="checkbox"/> 02.127.136	36 mm
<input type="checkbox"/> 02.127.138	38 mm
<input type="checkbox"/> 02.127.140	40 mm
<input type="checkbox"/> 02.127.142	42 mm
<input type="checkbox"/> 02.127.144	44 mm
<input type="checkbox"/> 02.127.146	46 mm
<input type="checkbox"/> 02.127.148	48 mm
<input type="checkbox"/> 02.127.150	50 mm
<input type="checkbox"/> 02.127.152	52 mm
<input type="checkbox"/> 02.127.154	54 mm
<input type="checkbox"/> 02.127.156	56 mm
<input type="checkbox"/> 02.127.158	58 mm
<input type="checkbox"/> 02.127.160	60 mm
<input type="checkbox"/> 02.127.165	65 mm
<input type="checkbox"/> 02.127.170	70 mm
<input type="checkbox"/> 02.127.175	75 mm
<input type="checkbox"/> 02.127.180	80 mm
<input type="checkbox"/> 02.127.185	85 mm
<input type="checkbox"/> 02.127.190	90 mm
<input type="checkbox"/> 02.127.195	95 mm

◊ Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile pouch or "TS" for sterile tube.

Inventory Control Form





RFN-ADVANCED™



Retrograde Femoral Nailing System

Instruments

◊ Available non sterile and sterile packed.
Add "S" to catalog number to order sterile product.

Drill Bits◊

Part #	Description
<input type="checkbox"/> 03.233.001◊	Ø 12.8 mm Drill Bit, Cannulated, Large QC
	
<input type="checkbox"/> 03.233.002◊	Ø 11.2 mm Drill Bit, Cannulated, Large QC
	
<input type="checkbox"/> 03.010.061◊	Ø 4.2 mm Drill Bit, 100 mm Calibration, QC
	
<input type="checkbox"/> 03.045.022◊	Ø 4.2 mm Drill Bit, Calibrated, QC, Extra Long
	

Part #	Description
<input type="checkbox"/> 03.010.101◊	Ø 4.2 mm Drill Bit, Length 145 mm, with Coupling for RDL
	
<input type="checkbox"/> 03.010.104◊	Ø 4.2 mm Drill Bit, Length 145 mm, Quick Coupling
	

Reaming and Guide Rods

Part #	Description
<input type="checkbox"/> 351.704S	2.5 mm Reaming Rod w/Ball Tip and Extension, 1150 mm, Sterile
<input type="checkbox"/> 351.706S	2.5 mm Reaming Rod w/Ball Tip, 950 mm, Sterile
<input type="checkbox"/> 351.707S	2.5 mm Reaming Rod w/Ball Tip and Extension, 950 mm, Sterile
<input type="checkbox"/> 351.708S	2.5 mm Reaming Rod w/Ball Tip, 1150 mm, Sterile
<input type="checkbox"/> 03.233.010S	3.0 mm Reaming Rod w/3.8 mm Ball Tip, 950 mm, Sterile
<input type="checkbox"/> 03.233.011S	3.0 mm Reaming Rod w/3.8 mm Ball Tip, 1150 mm, Sterile

Guide Wires

Part #	Description
<input type="checkbox"/> 357.399	3.2 mm Guide Wire, 400 mm
<input type="checkbox"/> 03.045.018◊	3.2 mm Guide Wire, Drill Tip, 400 mm