

Inventory Control Form

3.5/4.5 MM VA LCP™ PERIPROSTHETIC PROXIMAL FEMUR PLATING SYSTEM

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 844-243-4321

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

3.5/4.5 mm VA-LCP PPFx Proximal Femur Plates, LEFT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.111S*	2 holes	119 mm
<input type="checkbox"/>	02.221.113	7 holes	216 mm
<input type="checkbox"/>	02.221.115	8 holes	251 mm
<input type="checkbox"/>	02.221.121	9 holes	285 mm
<input type="checkbox"/>	02.221.123	10 holes	320 mm
<input type="checkbox"/>	02.221.125	11 holes	354 mm
<input type="checkbox"/>	02.221.131S*	12 holes	388 mm

3.5/4.5 mm VA-LCP PPFx Proximal Femur Plates, RIGHT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.110S*	2 holes	119 mm
<input type="checkbox"/>	02.221.112	7 holes	216 mm
<input type="checkbox"/>	02.221.114	8 holes	251 mm
<input type="checkbox"/>	02.221.120	9 holes	285 mm
<input type="checkbox"/>	02.221.122	10 holes	320 mm
<input type="checkbox"/>	02.221.124	11 holes	354 mm
<input type="checkbox"/>	02.221.130S*	12 holes	388 mm

3.5 mm VA-Locking PPFx Greater Trochanter Ring Attachment Plates, LEFT, SSt

	Size
<input type="checkbox"/>	02.221.101 SMALL
<input type="checkbox"/>	02.221.103 LARGE



3.5 mm VA-Locking PPFx Greater Trochanter Ring Attachment Plates, RIGHT, SSt

	Size
<input type="checkbox"/>	02.221.100 SMALL
<input type="checkbox"/>	02.221.102 LARGE



Replacement Connecting Screw for VA-Locking PPFx Greater Trochanter Ring Attachment Plates, sterile, SSt:

02.221.180S*



* Optional item.

Inventory Control Form

3.5/4.5 MM VA LCP™ PERIPROSTHETIC PROXIMAL FEMUR PLATING SYSTEM

Implants (cont'd)

3.5/4.5 mm VA-LCP PPFx Proximal Femur Hook Plates, SMALL, LEFT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.085	5 holes	211 mm
<input type="checkbox"/>	02.221.089	8 holes	285 mm
<input type="checkbox"/>	02.221.093	10 holes	354 mm

3.5/4.5 mm VA-LCP PPFx Proximal Femur Hook Plates, SMALL, RIGHT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.084	5 holes	211 mm
<input type="checkbox"/>	02.221.088	8 holes	285 mm
<input type="checkbox"/>	02.221.092	10 holes	354 mm

3.5/4.5 mm VA-LCP PPFx Proximal Femur Hook Plates, LARGE, LEFT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.087	5 holes	217 mm
<input type="checkbox"/>	02.221.091	8 holes	291 mm
<input type="checkbox"/>	02.221.095	10 holes	360 mm

3.5/4.5 mm VA-LCP PPFx Proximal Femur Hook Plates, LARGE, RIGHT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.086	5 holes	217 mm
<input type="checkbox"/>	02.221.090	8 holes	291 mm
<input type="checkbox"/>	02.221.094	10 holes	360 mm

3.5 mm VA-Locking PPFx Greater Trochanter Hook Plates, SSt

		Size
<input type="checkbox"/>	02.221.080 [◇]	SMALL
<input type="checkbox"/>	02.221.082 [◇]	LARGE



3.5 mm VA-Locking PPFx Distal Femur Spanning Attachment Plates, LEFT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.151	4 holes	142 mm
<input type="checkbox"/>	02.221.153	4 holes LONG	152 mm
<input type="checkbox"/>	02.221.155S*	6 holes	182 mm

3.5 mm VA-Locking PPFx Distal Femur Spanning Attachment Plates, RIGHT, SSt



		Holes	Length
<input type="checkbox"/>	02.221.150	4 holes	142 mm
<input type="checkbox"/>	02.221.152	4 holes LONG	152 mm
<input type="checkbox"/>	02.221.154S*	6 holes	182 mm

3.5 mm VA-Locking Attachment Plate, SSt

		Holes
<input type="checkbox"/>	02.221.174 [◇]	4 holes



Connecting Screw, SSt

Used for 3.5 mm VA-Locking Attachment Plate (1x) and 3.5 mm VA-Locking PPFx Distal Femur Spanning Attachment Plates (2x)

<input type="checkbox"/>	02.120.606 [◇]
--------------------------	-------------------------



* Optional item.

[◇] Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.

Inventory Control Form

3.5/4.5 MM VA LCP™ PERIPROSTHETIC PROXIMAL FEMUR PLATING SYSTEM

Screws

3.5 mm Variable Angle Locking Screws, StarDrive 15, SS†



		Length
<input type="checkbox"/>	02.127.110	10 mm
<input type="checkbox"/>	02.127.112	12 mm
<input type="checkbox"/>	02.127.114	14 mm
<input type="checkbox"/>	02.127.116	16 mm
<input type="checkbox"/>	02.127.118	18 mm
<input type="checkbox"/>	02.127.120	20 mm
<input type="checkbox"/>	02.127.122	22 mm
<input type="checkbox"/>	02.127.124	24 mm
<input type="checkbox"/>	02.127.126	26 mm
<input type="checkbox"/>	02.127.128	28 mm
<input type="checkbox"/>	02.127.130	30 mm
<input type="checkbox"/>	02.127.132	32 mm
<input type="checkbox"/>	02.127.134	34 mm
<input type="checkbox"/>	02.127.136	36 mm
<input type="checkbox"/>	02.127.138	38 mm
<input type="checkbox"/>	02.127.140	40 mm
<input type="checkbox"/>	02.127.142	42 mm
<input type="checkbox"/>	02.127.144	44 mm
<input type="checkbox"/>	02.127.146	46 mm
<input type="checkbox"/>	02.127.148	48 mm
<input type="checkbox"/>	02.127.150	50 mm
<input type="checkbox"/>	02.127.152	52 mm
<input type="checkbox"/>	02.127.154	54 mm
<input type="checkbox"/>	02.127.156	56 mm
<input type="checkbox"/>	02.127.158	58 mm
<input type="checkbox"/>	02.127.160	60 mm
<input type="checkbox"/>	02.127.165	65 mm
<input type="checkbox"/>	02.127.170	70 mm
<input type="checkbox"/>	02.127.175	75 mm
<input type="checkbox"/>	02.127.180	80 mm
<input type="checkbox"/>	02.127.185	85 mm
<input type="checkbox"/>	02.127.190	90 mm

3.5 mm Cortex Screws, StarDrive 15, SS†



		Length
<input type="checkbox"/>	02.200.010	10 mm
<input type="checkbox"/>	02.200.012	12 mm
<input type="checkbox"/>	02.200.014	14 mm
<input type="checkbox"/>	02.200.016	16 mm
<input type="checkbox"/>	02.200.018	18 mm
<input type="checkbox"/>	02.200.020	20 mm
<input type="checkbox"/>	02.200.022	22 mm
<input type="checkbox"/>	02.200.024	24 mm
<input type="checkbox"/>	02.200.026	26 mm
<input type="checkbox"/>	02.200.028	28 mm
<input type="checkbox"/>	02.200.030	30 mm
<input type="checkbox"/>	02.200.032	32 mm
<input type="checkbox"/>	02.200.034	34 mm
<input type="checkbox"/>	02.200.036	36 mm
<input type="checkbox"/>	02.200.038	38 mm
<input type="checkbox"/>	02.200.040	40 mm
<input type="checkbox"/>	02.200.042	42 mm
<input type="checkbox"/>	02.200.044	44 mm
<input type="checkbox"/>	02.200.046	46 mm
<input type="checkbox"/>	02.200.048	48 mm
<input type="checkbox"/>	02.200.050	50 mm
<input type="checkbox"/>	02.200.055	55 mm
<input type="checkbox"/>	02.200.060	60 mm
<input type="checkbox"/>	02.200.065*	65 mm
<input type="checkbox"/>	02.200.070*	70 mm
<input type="checkbox"/>	02.200.075*	75 mm
<input type="checkbox"/>	02.200.080*	80 mm
<input type="checkbox"/>	02.200.085*	85 mm
<input type="checkbox"/>	02.200.090*	90 mm

* Optional item.

† Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.

Inventory Control Form

3.5/4.5 MM VA LCP™ PERIPROSTHETIC PROXIMAL FEMUR PLATING SYSTEM

Screws (cont'd)

5.0 mm Variable Angle Locking (PPFx) Screws, StarDrive 25, SSt[◇]



		Length
	02.231.010	10 mm (PPFx)
	02.231.012	12 mm (PPFx)
	02.231.014	14 mm (PPFx)
	02.231.016	16 mm (PPFx)
	02.231.018	18 mm (PPFx)
	02.231.220	20 mm
	02.231.222	22 mm
	02.231.224	24 mm
	02.231.226	26 mm
	02.231.228	28 mm
	02.231.230	30 mm
	02.231.232	32 mm
	02.231.234	34 mm
	02.231.236	36 mm
	02.231.238	38 mm
	02.231.240	40 mm
	02.231.242	42 mm
	02.231.244	44 mm
	02.231.246	46 mm
	02.231.248	48 mm
	02.231.250	50 mm
	02.231.255	55 mm
	02.231.260	60 mm
	02.231.265*	65 mm
	02.231.270*	70 mm
	02.231.275*	75 mm
	02.231.280*	80 mm
	02.231.285*	85 mm
	02.231.290*	90 mm

4.5 mm Cortex Screws, 3.5 mm Hex, SSt[◇]



		Length
	214.820	20 mm
	214.822	22 mm
	214.824	24 mm
	214.826	26 mm
	214.828	28 mm
	214.830	30 mm
	214.832	32 mm
	214.834	34 mm
	214.836	36 mm
	214.838	38 mm
	214.840	40 mm
	214.842	42 mm
	214.844	44 mm
	214.846	46 mm
	214.848	48 mm
	214.850	50 mm
	214.852	52 mm
	214.854	54 mm
	214.856	56 mm
	214.858	58 mm
	214.860	60 mm
	214.862*	62 mm
	214.864*	64 mm
	214.866*	66 mm
	214.868*	68 mm
	214.870*	70 mm
	214.872*	72 mm
	214.876*	76 mm
	214.880*	80 mm
	214.885*	85 mm
	214.890*	90 mm

* Optional item.

◇ Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.

Inventory Control Form

3.5/4.5 MM VA LCP™ PERIPROSTHETIC PROXIMAL FEMUR PLATING SYSTEM

Cables

1.7 mm Cable, SSt, sterile

		Pack
<input type="checkbox"/>	298.801.01S	Single pack
<input type="checkbox"/>	298.801.10S	10 pack

Additionally Available Implants for Cables, sterile (optional)

<input type="checkbox"/>	02.231.022S*	5.0 mm VA Positioning Pin
<input type="checkbox"/>	02.221.002S*	Cerclage Button, StarDrive 15 / 2.5mm Hex
<input type="checkbox"/>	02.221.003S*	Cerclage Button, StarDrive 25 / 3.5mm Hex

Drill Bits

Drill Bits for 3.5 mm Cortex Screws / 3.5 mm VA Locking Screws

<input type="checkbox"/>	03.133.103*	2.5 mm Drill Bit/Quick Coupling 170 mm, 80 mm Calibration
<input type="checkbox"/>	03.133.104	2.5 mm Drill Bit/Quick Coupling 240 mm, 150 mm Calibration
<input type="checkbox"/>	03.133.107*	2.8 mm Drill Bit/Quick Coupling 170 mm, 80 mm Calibration
<input type="checkbox"/>	03.133.108	2.8 mm Drill Bit/Quick Coupling 200 mm, 110 mm Calibration
<input type="checkbox"/>	03.133.109*	3.5 mm Drill Bit/Quick Coupling 150 mm

Drill Bits for 4.5 mm Cortex Screws / 5.0 mm VA Locking Screws

<input type="checkbox"/>	315.93	3.2 mm Drill Bit, calibrated, length 230/205 mm, 3-flute, for Quick Coupling
<input type="checkbox"/>	310.31*	3.2 mm Drill Bit, length 145/120 mm, 2-flute, for Quick Coupling
<input type="checkbox"/>	310.431	4.3 mm Drill Bit, 180 mm, quick coupling
<input type="checkbox"/>	324.213*	4.3 mm Percutaneous Drill Bit, quick coupling, 300 mm, calibrated
<input type="checkbox"/>	310.44*	4.5 mm Drill Bit, 145 mm, quick coupling

Wires

<input type="checkbox"/>	310.243	2.5 mm Drill Tip Guide Wire, length 200 mm
<input type="checkbox"/>	03.120.026*	2.5 mm Drill Tip Guide Wire, 300 mm
<input type="checkbox"/>	338.002*	2.5 mm Drill Tip Guide Wire, 300 mm
<input type="checkbox"/>	03.118.020*	2.8 mm Compression Wire, length 200 mm

* Optional item

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.