

# Inventory Control Form

## 4.5 mm VA LCP™ Curved Condylar Plate System

Case Information (eg, Case ID):

DO NOT PUT ANY  
PATIENT IDENTIFIABLE  
INFORMATION IN  
THIS FIELD

To order (USA): 800-523-0322

To order (Canada): 844-243-4321

Date: \_\_\_\_\_

Hospital: \_\_\_\_\_

Surgeon: \_\_\_\_\_

Procedure: \_\_\_\_\_

### Implants

#### Variable Angle Plates

##### 4.5 mm VA LCP Curved Condylar Plates

Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.



|                          |            | Holes     | Length |
|--------------------------|------------|-----------|--------|
| <input type="checkbox"/> | 02.124.406 | 6, Right  | 159 mm |
| <input type="checkbox"/> | 02.124.407 | 6, Left   | 159 mm |
| <input type="checkbox"/> | 02.124.408 | 8, Right  | 195 mm |
| <input type="checkbox"/> | 02.124.409 | 8, Left   | 195 mm |
| <input type="checkbox"/> | 02.124.410 | 10, Right | 230 mm |
| <input type="checkbox"/> | 02.124.411 | 10, Left  | 230 mm |
| <input type="checkbox"/> | 02.124.412 | 12, Right | 266 mm |
| <input type="checkbox"/> | 02.124.413 | 12, Left  | 266 mm |
| <input type="checkbox"/> | 02.124.414 | 14, Right | 301 mm |
| <input type="checkbox"/> | 02.124.415 | 14, Left  | 301 mm |
| <input type="checkbox"/> | 02.124.416 | 16, Right | 336 mm |
| <input type="checkbox"/> | 02.124.417 | 16, Left  | 336 mm |
| <input type="checkbox"/> | 02.124.418 | 18, Right | 370 mm |
| <input type="checkbox"/> | 02.124.419 | 18, Left  | 370 mm |

##### The following products are available sterile only:

|                          |             |           |        |
|--------------------------|-------------|-----------|--------|
| <input type="checkbox"/> | 02.124.420S | 20, Right | 405 mm |
| <input type="checkbox"/> | 02.124.421S | 20, Left  | 405 mm |
| <input type="checkbox"/> | 02.124.422S | 22, Right | 439 mm |
| <input type="checkbox"/> | 02.124.423S | 22, Left  | 439 mm |

#### Variable Angle Screws:

##### 5.0 mm Periprosthetic Variable Angle Locking Screws, Self-Tapping, T25 StarDrive™

Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.



|                          |            | Length |
|--------------------------|------------|--------|
| <input type="checkbox"/> | 02.231.010 | 10 mm  |
| <input type="checkbox"/> | 02.231.012 | 12 mm  |
| <input type="checkbox"/> | 02.231.014 | 14 mm  |
| <input type="checkbox"/> | 02.231.016 | 16 mm  |
| <input type="checkbox"/> | 02.231.018 | 18 mm  |

##### The following product is available sterile only:

|                          |             |      |
|--------------------------|-------------|------|
| <input type="checkbox"/> | 02.231.008S | 8 mm |
|--------------------------|-------------|------|

##### 5.0 mm Variable Angle Locking Screws, Self-Tapping, T25 StarDrive™



|                          |            | Length |                          |            | Length |
|--------------------------|------------|--------|--------------------------|------------|--------|
| <input type="checkbox"/> | 02.231.214 | 14 mm  | <input type="checkbox"/> | 02.231.242 | 42 mm  |
| <input type="checkbox"/> | 02.231.216 | 16 mm  | <input type="checkbox"/> | 02.231.244 | 44 mm  |
| <input type="checkbox"/> | 02.231.218 | 18 mm  | <input type="checkbox"/> | 02.231.246 | 46 mm  |
| <input type="checkbox"/> | 02.231.220 | 20 mm  | <input type="checkbox"/> | 02.231.248 | 48 mm  |
| <input type="checkbox"/> | 02.231.222 | 22 mm  | <input type="checkbox"/> | 02.231.250 | 50 mm  |
| <input type="checkbox"/> | 02.231.224 | 24 mm  | <input type="checkbox"/> | 02.231.255 | 55 mm  |
| <input type="checkbox"/> | 02.231.226 | 26 mm  | <input type="checkbox"/> | 02.231.260 | 60 mm  |
| <input type="checkbox"/> | 02.231.228 | 28 mm  | <input type="checkbox"/> | 02.231.265 | 65 mm  |
| <input type="checkbox"/> | 02.231.230 | 30 mm  | <input type="checkbox"/> | 02.231.270 | 70 mm  |
| <input type="checkbox"/> | 02.231.232 | 32 mm  | <input type="checkbox"/> | 02.231.275 | 75 mm  |
| <input type="checkbox"/> | 02.231.234 | 34 mm  | <input type="checkbox"/> | 02.231.280 | 80 mm  |
| <input type="checkbox"/> | 02.231.236 | 36 mm  | <input type="checkbox"/> | 02.231.285 | 85 mm  |
| <input type="checkbox"/> | 02.231.238 | 38 mm  | <input type="checkbox"/> | 02.231.290 | 90 mm  |
| <input type="checkbox"/> | 02.231.240 | 40 mm  |                          |            |        |

##### The following products are available sterile only:

|                          |             |        |                          |             |        |
|--------------------------|-------------|--------|--------------------------|-------------|--------|
| <input type="checkbox"/> | 02.231.295S | 95 mm  | <input type="checkbox"/> | 02.231.305S | 105 mm |
| <input type="checkbox"/> | 02.231.300S | 100 mm | <input type="checkbox"/> | 02.231.310S | 110 mm |

##### 5.0 mm Cannulated Variable Angle Locking Screws, 4.0 mm Hex



|                          |            | Length |                          |            | Length |
|--------------------------|------------|--------|--------------------------|------------|--------|
| <input type="checkbox"/> | 02.231.620 | 20 mm  | <input type="checkbox"/> | 02.231.660 | 60 mm  |
| <input type="checkbox"/> | 02.231.625 | 25 mm  | <input type="checkbox"/> | 02.231.665 | 65 mm  |
| <input type="checkbox"/> | 02.231.630 | 30 mm  | <input type="checkbox"/> | 02.231.670 | 70 mm  |
| <input type="checkbox"/> | 02.231.635 | 35 mm  | <input type="checkbox"/> | 02.231.675 | 75 mm  |
| <input type="checkbox"/> | 02.231.640 | 40 mm  | <input type="checkbox"/> | 02.231.680 | 80 mm  |
| <input type="checkbox"/> | 02.231.645 | 45 mm  | <input type="checkbox"/> | 02.231.685 | 85 mm  |
| <input type="checkbox"/> | 02.231.650 | 50 mm  | <input type="checkbox"/> | 02.231.690 | 90 mm  |
| <input type="checkbox"/> | 02.231.655 | 55 mm  |                          |            |        |

##### The following products are available sterile only:

|                          |             |        |                          |             |        |
|--------------------------|-------------|--------|--------------------------|-------------|--------|
| <input type="checkbox"/> | 02.231.695S | 95 mm  | <input type="checkbox"/> | 02.231.705S | 105 mm |
| <input type="checkbox"/> | 02.231.700S | 100 mm | <input type="checkbox"/> | 02.231.710S | 110 mm |

# Inventory Control Form

## 4.5 mm VA LCP™ Curved Condylar Plate System

### Implants (cont'd)

#### 4.5 mm Cortex Screws, self tapping, 3.5 Hex



|                          | Length  |                          | Length  |
|--------------------------|---------|--------------------------|---------|
| <input type="checkbox"/> | 214.822 | <input type="checkbox"/> | 214.848 |
| <input type="checkbox"/> | 214.824 | <input type="checkbox"/> | 214.850 |
| <input type="checkbox"/> | 214.826 | <input type="checkbox"/> | 214.852 |
| <input type="checkbox"/> | 214.828 | <input type="checkbox"/> | 214.854 |
| <input type="checkbox"/> | 214.830 | <input type="checkbox"/> | 214.856 |
| <input type="checkbox"/> | 214.832 | <input type="checkbox"/> | 214.858 |
| <input type="checkbox"/> | 214.834 | <input type="checkbox"/> | 214.860 |
| <input type="checkbox"/> | 214.836 | <input type="checkbox"/> | 214.862 |
| <input type="checkbox"/> | 214.838 | <input type="checkbox"/> | 214.864 |
| <input type="checkbox"/> | 214.840 | <input type="checkbox"/> | 214.866 |
| <input type="checkbox"/> | 214.842 | <input type="checkbox"/> | 214.868 |
| <input type="checkbox"/> | 214.844 | <input type="checkbox"/> | 214.870 |
| <input type="checkbox"/> | 214.846 |                          |         |

#### 5.0 mm Variable Angle Locking Screws, OPTILINK™, self-tapping, T25 StarDrive



|                          | Length     |                          | Length     |
|--------------------------|------------|--------------------------|------------|
| <input type="checkbox"/> | 42.231.214 | <input type="checkbox"/> | 42.231.242 |
| <input type="checkbox"/> | 42.231.216 | <input type="checkbox"/> | 42.231.244 |
| <input type="checkbox"/> | 42.231.218 | <input type="checkbox"/> | 42.231.246 |
| <input type="checkbox"/> | 42.231.220 | <input type="checkbox"/> | 42.231.248 |
| <input type="checkbox"/> | 42.231.222 | <input type="checkbox"/> | 42.231.250 |
| <input type="checkbox"/> | 42.231.224 | <input type="checkbox"/> | 42.231.255 |
| <input type="checkbox"/> | 42.231.226 | <input type="checkbox"/> | 42.231.260 |
| <input type="checkbox"/> | 42.231.228 | <input type="checkbox"/> | 42.231.265 |
| <input type="checkbox"/> | 42.231.230 | <input type="checkbox"/> | 42.231.270 |
| <input type="checkbox"/> | 42.231.232 | <input type="checkbox"/> | 42.231.275 |
| <input type="checkbox"/> | 42.231.234 | <input type="checkbox"/> | 42.231.280 |
| <input type="checkbox"/> | 42.231.236 | <input type="checkbox"/> | 42.231.285 |
| <input type="checkbox"/> | 42.231.238 | <input type="checkbox"/> | 42.231.290 |
| <input type="checkbox"/> | 42.231.240 |                          |            |

#### The following products are available sterile only:

|                          |             |        |                          |             |        |
|--------------------------|-------------|--------|--------------------------|-------------|--------|
| <input type="checkbox"/> | 42.231.295S | 95 mm  | <input type="checkbox"/> | 42.231.305S | 105 mm |
| <input type="checkbox"/> | 42.231.300S | 100 mm | <input type="checkbox"/> | 42.231.310S | 110 mm |

#### 5.0 mm Cannulated Variable Angle Locking Screws, OPTILINK™



|                          | Length     |                          | Length     |
|--------------------------|------------|--------------------------|------------|
| <input type="checkbox"/> | 42.231.620 | <input type="checkbox"/> | 42.231.660 |
| <input type="checkbox"/> | 42.231.625 | <input type="checkbox"/> | 42.231.665 |
| <input type="checkbox"/> | 42.231.630 | <input type="checkbox"/> | 42.231.670 |
| <input type="checkbox"/> | 42.231.635 | <input type="checkbox"/> | 42.231.675 |
| <input type="checkbox"/> | 42.231.640 | <input type="checkbox"/> | 42.231.680 |
| <input type="checkbox"/> | 42.231.645 | <input type="checkbox"/> | 42.231.685 |
| <input type="checkbox"/> | 42.231.650 | <input type="checkbox"/> | 42.231.690 |
| <input type="checkbox"/> | 42.231.655 |                          |            |

#### The following products are available sterile only:

|                          |             |        |                          |             |        |
|--------------------------|-------------|--------|--------------------------|-------------|--------|
| <input type="checkbox"/> | 42.231.695S | 95 mm  | <input type="checkbox"/> | 42.231.705S | 105 mm |
| <input type="checkbox"/> | 42.231.700S | 100 mm | <input type="checkbox"/> | 42.231.710S | 110 mm |

#### 5.0 mm Periprosthesis Variable Angle Locking Screws, OPTILINK™, self-tapping, T25 StarDrive™

Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.



|                          | Length     |                          | Length     |
|--------------------------|------------|--------------------------|------------|
| <input type="checkbox"/> | 42.231.010 | <input type="checkbox"/> | 42.231.016 |
| <input type="checkbox"/> | 42.231.012 | <input type="checkbox"/> | 42.231.018 |
| <input type="checkbox"/> | 42.231.014 |                          |            |

#### The following product is available sterile only:

|                          |             |      |
|--------------------------|-------------|------|
| <input type="checkbox"/> | 42.231.008S | 8 mm |
|--------------------------|-------------|------|

## Instruments

#### Drill Bits and Wires

|                          |            |  |
|--------------------------|------------|--|
| <input type="checkbox"/> | 310.243    | 2.5 mm Drill Tip Guide Wire, 200 mm                          |
| <input type="checkbox"/> | 310.31     | 3.2 mm Drill Bit, 145 mm, quick coupling                     |
| <input type="checkbox"/> | 310.431    | 4.3 mm Drill Bit, 180 mm, quick coupling                     |
| <input type="checkbox"/> | 324.212    | 3.2 mm Percutaneous Drill Bit QC/300 mm/ calibrated          |
| <input type="checkbox"/> | 324.213    | 4.3 mm Percutaneous Drill Bit QC/300 mm/ calibrated          |
| <input type="checkbox"/> | 292.652    | 2.0 mm Non colored, threaded guide wire, spade point, 230 mm |
| <input type="checkbox"/> | 310.44     | 4.5 mm Drill Bit, 145 mm, quick coupling                     |
| <input type="checkbox"/> | 310.634    | 4.3 mm Cannulated Drill Bit, quick coupling, 200 mm          |
| <input type="checkbox"/> | 310.632    | 5.0 Cannulated Drill Bit, quick coupling, 200 mm             |
| <input type="checkbox"/> | 03.120.026 | 2.5 mm Drill Tip Guide Wire, 300 mm                          |

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.