

INVENTORY CONTROL FORM

TOMOFIX® Osteotomy System

Patient Information:

Synthes (USA) To order: (800) 523-0322	Synthes (Canada) Ltd. To order: (800) 668-1119
--	--

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

5.0 mm Titanium Locking Head Screws, self-tapping



	LENGTH		LENGTH		
<input type="checkbox"/>	413.324	24 mm	<input type="checkbox"/>	413.346	46 mm
<input type="checkbox"/>	413.326	26 mm	<input type="checkbox"/>	413.348	48 mm
<input type="checkbox"/>	413.328	28 mm	<input type="checkbox"/>	413.350	50 mm
<input type="checkbox"/>	413.330	30 mm	<input type="checkbox"/>	413.355	55 mm
<input type="checkbox"/>	413.332	32 mm	<input type="checkbox"/>	413.360	60 mm
<input type="checkbox"/>	413.334	34 mm	<input type="checkbox"/>	413.365	65 mm
<input type="checkbox"/>	413.336	36 mm	<input type="checkbox"/>	413.370	70 mm
<input type="checkbox"/>	413.338	38 mm	<input type="checkbox"/>	413.375	75 mm
<input type="checkbox"/>	413.340	40 mm	<input type="checkbox"/>	413.380	80 mm
<input type="checkbox"/>	413.342	42 mm	<input type="checkbox"/>	413.385	85 mm
<input type="checkbox"/>	413.344	44 mm	<input type="checkbox"/>	413.390	90 mm

5.0 mm Titanium Locking Head Screws, self-drilling



	LENGTH
<input type="checkbox"/>	413.426 26 mm

5.0 mm Titanium Spacer



	LENGTH
<input type="checkbox"/>	413.309 2 mm

4.5 mm Titanium Cortex Screws, self-tapping



	LENGTH		LENGTH		
<input type="checkbox"/>	414.824	24 mm	<input type="checkbox"/>	414.840	40 mm
<input type="checkbox"/>	414.826	26 mm	<input type="checkbox"/>	414.842	42 mm
<input type="checkbox"/>	414.828	28 mm	<input type="checkbox"/>	414.844	44 mm
<input type="checkbox"/>	414.830	30 mm	<input type="checkbox"/>	414.846	46 mm
<input type="checkbox"/>	414.832	32 mm	<input type="checkbox"/>	414.848	48 mm
<input type="checkbox"/>	414.834	34 mm	<input type="checkbox"/>	414.850	50 mm
<input type="checkbox"/>	414.836	36 mm	<input type="checkbox"/>	414.852	52 mm
<input type="checkbox"/>	414.838	38 mm			

Titanium TOMOFIX® Tibia Plates



<input type="checkbox"/>	440.834	Medial High, 4 holes
<input type="checkbox"/>	440.831	Medial High, small, 4 holes

<input type="checkbox"/>	440.843	Lateral High, 3 holes, right
<input type="checkbox"/>	440.853	Lateral High, 3 holes, left



Titanium TOMOFIX® Femur Plates

<input type="checkbox"/>	440.864	Lateral Distal, 4 holes, right
<input type="checkbox"/>	440.874	Lateral Distal, 4 holes, left



<input type="checkbox"/>	440.885 [◇]	Medial Distal, 4 holes, right
<input type="checkbox"/>	440.895 [◇]	Medial Distal, 4 holes, left



<input type="checkbox"/>	04.120.550 [◇]	Medial Distal, 4 holes, right
<input type="checkbox"/>	04.120.551 [◇]	Medial Distal, 4 holes, left



Drill Bits and K-Wires

	LENGTH
<input type="checkbox"/>	292.21 2.0 mm K-Wire w/trocar point, 285 mm, 10/pkg.
<input type="checkbox"/>	292.76 2.5 mm K-Wire, w/15 mm threaded trocar point, 200 mm, 10/pkg.
<input type="checkbox"/>	292.699 2.0 mm K-Wire, threaded spade point tip, 280 mm
<input type="checkbox"/>	310.430 4.3 mm Drill Bit, Quick Coupling, 221 mm
<input type="checkbox"/>	310.31 3.2 mm Drill Bit, Quick Coupling, 145 mm
<input type="checkbox"/>	310.243 2.5 mm Drill Tip Guide Wire, 200 mm
<input type="checkbox"/>	02.108.200 3.0 mm Drill Tip Guide Wire w/threads, 230 mm

[◇]Available nonsterile or sterile-packed. Add "S" to catalog number to order sterile product.