

Inventory Control Form

3.5 mm Low Profile Pelvic System

Case Information (eg, Case ID):

DO NOT PUT ANY
PATIENT IDENTIFIABLE
INFORMATION IN
THIS FIELD

To order (USA): 800-523-0322
To order (Canada): 844-243-4321

Date: _____

Hospital: _____

Surgeon: _____

Procedure: _____

Implants

3.5 mm Pelvic Cortex Screws, self-tapping



	Length		Length		
<input type="checkbox"/>	204.640	40 mm	<input type="checkbox"/>	204.700	100 mm
<input type="checkbox"/>	204.645	45 mm	<input type="checkbox"/>	204.705	105 mm
<input type="checkbox"/>	204.650	50 mm	<input type="checkbox"/>	204.710	110 mm
<input type="checkbox"/>	204.655	55 mm	<input type="checkbox"/>	204.715	115 mm
<input type="checkbox"/>	204.660	60 mm	<input type="checkbox"/>	204.720	120 mm
<input type="checkbox"/>	204.665	65 mm	<input type="checkbox"/>	204.725	125 mm
<input type="checkbox"/>	204.670	70 mm	<input type="checkbox"/>	204.730	130 mm
<input type="checkbox"/>	204.675	75 mm	<input type="checkbox"/>	204.735	135 mm
<input type="checkbox"/>	204.680	80 mm	<input type="checkbox"/>	204.740	140 mm
<input type="checkbox"/>	204.685	85 mm	<input type="checkbox"/>	204.745	145 mm
<input type="checkbox"/>	204.690	90 mm	<input type="checkbox"/>	204.750	150 mm
<input type="checkbox"/>	204.695	95 mm			

3.5 mm Locking Screws, self-tapping, with StarDrive™ Recess



	Length		Length		
<input type="checkbox"/>	212.101	10 mm	<input type="checkbox"/>	212.117	40 mm
<input type="checkbox"/>	212.102	12 mm	<input type="checkbox"/>	212.118	42 mm
<input type="checkbox"/>	212.103	14 mm	<input type="checkbox"/>	212.119	45 mm
<input type="checkbox"/>	212.104	16 mm	<input type="checkbox"/>	212.120	48 mm
<input type="checkbox"/>	212.105	18 mm	<input type="checkbox"/>	212.121	50 mm
<input type="checkbox"/>	212.106	20 mm	<input type="checkbox"/>	212.122	52 mm
<input type="checkbox"/>	212.107	22 mm	<input type="checkbox"/>	212.123	55 mm
<input type="checkbox"/>	212.108	24 mm	<input type="checkbox"/>	212.124	60 mm
<input type="checkbox"/>	212.109	26 mm	<input type="checkbox"/>	212.125	65 mm
<input type="checkbox"/>	212.110	28 mm	<input type="checkbox"/>	212.126	70 mm
<input type="checkbox"/>	212.111	30 mm	<input type="checkbox"/>	212.127	75 mm
<input type="checkbox"/>	212.112	32 mm	<input type="checkbox"/>	212.128	80 mm
<input type="checkbox"/>	212.113	34 mm	<input type="checkbox"/>	212.129	85 mm
<input type="checkbox"/>	212.114	35 mm	<input type="checkbox"/>	212.130	90 mm
<input type="checkbox"/>	212.115	36 mm	<input type="checkbox"/>	212.131	95 mm
<input type="checkbox"/>	212.116	38 mm			

3.5 mm Cortex Screws, self-tapping



	Length		Length		
<input type="checkbox"/>	204.810	10 mm	<input type="checkbox"/>	204.826	26 mm
<input type="checkbox"/>	204.812	12 mm	<input type="checkbox"/>	204.828	28 mm
<input type="checkbox"/>	204.814	14 mm	<input type="checkbox"/>	204.830	30 mm
<input type="checkbox"/>	204.816	16 mm	<input type="checkbox"/>	204.832	32 mm
<input type="checkbox"/>	204.818	18 mm	<input type="checkbox"/>	204.834	34 mm
<input type="checkbox"/>	204.820	20 mm	<input type="checkbox"/>	204.836	36 mm
<input type="checkbox"/>	204.822	22 mm	<input type="checkbox"/>	204.838	38 mm
<input type="checkbox"/>	204.824	24 mm			

3.5 mm Threaded Plug, StarDrive

(for protection of the 3.5 mm Threaded Plate holes during contouring)

02.200.003



3.5 mm Low Profile Pelvic System

Implants (cont'd)

3.5 mm Cortex Screws, self-tapping, with T15 StarDrive Recess



	Length		Length
	10 mm		50 mm
	12 mm		55 mm
	14 mm		60 mm
	16 mm		65 mm
	18 mm		70 mm
	20 mm		75 mm
	22 mm		80 mm
	24 mm		85 mm
	26 mm		90 mm
	28 mm		95 mm
	30 mm		100 mm
	32 mm		105 mm
	34 mm		110 mm
	36 mm		115 mm
	38 mm		120 mm
	40 mm		125 mm
	42 mm		130 mm
	44 mm		135 mm
	45 mm		140 mm
	46 mm		145 mm
	48 mm		150 mm

4.5 mm Cortex Screws (non self-tapping)



	Length		Length
	80 mm		125 mm
	85 mm		130 mm
	90 mm		135 mm
	95 mm		140 mm
	100 mm		145 mm
	105 mm		150 mm
	110 mm		155 mm
	115 mm		160 mm
	120 mm		

3.5 mm Low Profile Curved Reconstruction Plates



	88 mm radius		108 mm radius	Holes	Length
	245.906		245.876	6	78 mm
	245.908		245.878	8	104 mm
	245.910		245.880	10	130 mm
	245.912		245.882	12	156 mm
	245.914		245.884	14	182 mm
	245.916		245.886	16	208 mm

4.5 mm Cortex Screws, self-tapping



	Length		Length
	40 mm		72 mm
	42 mm		76 mm
	44 mm		80 mm
	46 mm		85 mm
	48 mm		90 mm
	50 mm		85 mm
	52 mm		100 mm
	54 mm		110 mm
	56 mm		115 mm
	58 mm		120 mm
	60 mm		125 mm
	62 mm		130 mm
	64 mm		135 mm
	66 mm		140 mm
	68 mm		145 mm
	70 mm		

3.5 mm Low Profile Reconstruction Plates



	Holes	Length
	3	39 mm
	4	52 mm
	5	65 mm
	6	78 mm
	7	91 mm
	8	104 mm
	9	117 mm
	10	130 mm
	11	143 mm
	12	156 mm
	13	169 mm
	14	182 mm
	15	195 mm
	16	208 mm
	18	234 mm
	20	260 mm

3.5 mm Spring Plates



	Holes		Holes	
	02.100.301	1	02.100.301S	1
	02.100.302	2	02.100.302S	2
	02.100.303	3	02.100.303S	3

3.5 mm Low Profile Pelvic System

Implants (cont'd)

3.5 mm Wide Angle Low Profile Reconstruction Plates



		Holes	Length
<input type="checkbox"/>	02.100.203	3	39 mm
<input type="checkbox"/>	02.100.204	4	52 mm
<input type="checkbox"/>	02.100.205	5	65 mm
<input type="checkbox"/>	02.100.206	6	78 mm
<input type="checkbox"/>	02.100.207	7	91 mm
<input type="checkbox"/>	02.100.208	8	104 mm
<input type="checkbox"/>	02.100.209	9	117 mm
<input type="checkbox"/>	02.100.210	10	130 mm
<input type="checkbox"/>	02.100.211	11	143 mm
<input type="checkbox"/>	02.100.212	12	156 mm
<input type="checkbox"/>	02.100.213	13	169 mm
<input type="checkbox"/>	02.100.214	14	182 mm
<input type="checkbox"/>	02.100.215	15	195 mm
<input type="checkbox"/>	02.100.216	16	208 mm
<input type="checkbox"/>	02.100.218	18	234 mm
<input type="checkbox"/>	02.100.220	20	260 mm

3.5 mm Low Profile Reconstruction J-Plates (88 mm radius)



Left	Right	Holes	Length
<input type="checkbox"/>	245.930	10	130 mm
<input type="checkbox"/>	245.932	12	156 mm
<input type="checkbox"/>	245.934	14	182 mm
<input type="checkbox"/>	245.936	16	208 mm

3.5 mm Locking Low Profile Reconstruction Plates



		Holes	Length
<input type="checkbox"/>	02.100.103	3	39 mm
<input type="checkbox"/>	02.100.104	4	52 mm
<input type="checkbox"/>	02.100.105	5	65 mm
<input type="checkbox"/>	02.100.106	6	78 mm
<input type="checkbox"/>	02.100.107	7	91 mm
<input type="checkbox"/>	02.100.108	8	104 mm
<input type="checkbox"/>	02.100.109	9	117 mm
<input type="checkbox"/>	02.100.110	10	130 mm
<input type="checkbox"/>	02.100.111	11	143 mm
<input type="checkbox"/>	02.100.112	12	156 mm
<input type="checkbox"/>	02.100.113	13	169 mm
<input type="checkbox"/>	02.100.114	14	182 mm
<input type="checkbox"/>	02.100.115	15	195 mm
<input type="checkbox"/>	02.100.116	16	208 mm
<input type="checkbox"/>	02.100.118	18	234 mm
<input type="checkbox"/>	02.100.120	20	260 mm

3.5 mm Low Profile Reconstruction J-Plates (88 mm radius)



Left	Right	Holes	Length
<input type="checkbox"/>	02.100.361	10	130 mm
<input type="checkbox"/>	02.100.363	12	156 mm
<input type="checkbox"/>	02.100.365	14	182 mm
<input type="checkbox"/>	02.100.367	16	208 mm

3.5 mm Pubic Symphysis Plate with 2 DCP™ Holes




	Holes	Length	
<input type="checkbox"/>	02.100.014	4	57 mm
<input type="checkbox"/>	02.100.016	6	78 mm

3.5 mm Pubic Symphysis Plate with Coaxial Combi Holes



	Holes	Length	
<input type="checkbox"/>	02.100.004	4	57 mm
<input type="checkbox"/>	02.100.006	6	78 mm

Miscellaneous Implants

<input type="checkbox"/>	219.98	Washer, 7.0 mm	
<input type="checkbox"/>	292.20	2.0 mm Kirschner wire, 150 mm, 10/pkg.	
<input type="checkbox"/>	294.68	6.0 mm Schanz Screw, 190 mm, spade point	

Inventory Control Form

3.5 mm Low Profile Pelvic System

Instruments

Drill Bits, quick coupling



		Diameter	Length
<input type="checkbox"/>	310.288	2.8 mm	165 mm
<input type="checkbox"/>	310.37	3.5 mm	195 mm
<input type="checkbox"/>	324.210	2.5 mm	300 mm, 200 mm calibration
<input type="checkbox"/>	324.211	2.8 mm	300 mm, 200 mm calibration

Three-Fluted Drill Bits, quick coupling



		Diameter	Length
<input type="checkbox"/>	315.92	2.5 mm	230 mm, 200 mm calibration
<input type="checkbox"/>	315.93	3.2 mm	230 mm, 200 mm calibration
<input type="checkbox"/>	315.48	4.5 mm	195 mm

Taps



<input type="checkbox"/>	311.31	for 3.5 mm Cortex Screws, 175 mm, 140 mm calibration
<input type="checkbox"/>	311.47	for 4.5 mm Cortex Screws, 175 mm, 140 mm calibration

Bending Templates



03.100.034 for 3.5 mm Low Profile Reconstruction Plates, 20 holes



03.100.035 for 3.5 mm Low Profile Reconstruction J-Pates, 16 holes



03.100.036 for 3.5 mm Low Profile Curved Reconstruction Plates, 88 mm radius, 16 holes



03.100.037 for 3.5 mm Low Profile Curved Reconstruction Plates, 108 mm radius, 16 holes

Some devices in this form may not have been licensed in accordance with Canadian law and may not be for sale in Canada. Please contact your sales consultant for items approved for sale in Canada.