

# Inventory Control Form

## Distal Radius Fixator



Patient Information:

SYNTHES (USA)  
To Order: (800) 523-0322

SYNTHES (Canada) Ltd.  
To Order: (800) 668-1119

Date: \_\_\_\_\_

Hospital: \_\_\_\_\_

Surgeon: \_\_\_\_\_

Procedure: \_\_\_\_\_

### Implants

#### Kirschner Wires with trocar point (10/pkg.)

		DIAMETER	LENGTH
<input type="checkbox"/>	292.16	1.6 mm	150 mm
<input type="checkbox"/>	292.20	2.0 mm	150 mm

#### Self-Drilling Schanz Screws (stainless steel)

		DIAMETER	LENGTH
<input type="checkbox"/>	294.767	4.0 mm/2.5 mm	65 mm
<input type="checkbox"/>	294.769	4.0 mm/2.5 mm	80 mm
<input type="checkbox"/>	294.771	4.0 mm/3.0 mm	80 mm
<input type="checkbox"/>	294.772	4.0 mm/3.0 mm	100 mm
<input type="checkbox"/>	294.773	4.0 mm/3.0 mm	65 mm
<input type="checkbox"/>	294.774	4.0 mm	60 mm
<input type="checkbox"/>	294.775	4.0 mm	80 mm
<input type="checkbox"/>	294.776	4.0 mm	100 mm

#### (titanium)

		DIAMETER	LENGTH
<input type="checkbox"/>	494.769	4.0 mm/2.5 mm	80 mm
<input type="checkbox"/>	494.771	4.0 mm/3.0 mm	80 mm
<input type="checkbox"/>	494.772	4.0 mm/3.0 mm	100 mm
<input type="checkbox"/>	494.774	4.0 mm	60 mm
<input type="checkbox"/>	494.775	4.0 mm	80 mm
<input type="checkbox"/>	494.776	4.0 mm	100 mm




#### Self-Drilling Schanz Screws Hydroxyapatite Coated, sterile (stainless steel)

		DIAMETER	LENGTH
<input type="checkbox"/>	294.771SHA	4.0/3.0 mm	80 mm
<input type="checkbox"/>	294.775SHA	4.0 mm	80 mm
<input type="checkbox"/>	294.776SHA	4.0 mm	100 mm


#### (titanium)

		DIAMETER	LENGTH
<input type="checkbox"/>	494.771SHA	4.0/3.0 mm	80 mm

### Fixation Material

<input type="checkbox"/>	390.051	4.0 mm Adjustable Clamp	
<input type="checkbox"/>	395.781	Protective Caps, for 8.0 mm Carbon Fiber Rods (black) (2/pkg.)	
<input type="checkbox"/>	394.991	Protective Caps, for 4.0 mm Fixation Pins (yellow) (10/pkg.)	

#### 8.0 mm Carbon Fiber Rods

<input type="checkbox"/>	395.782	200 mm	
<input type="checkbox"/>	395.784	220 mm	
<input type="checkbox"/>	395.786	240 mm	

#### 2.0 mm Drill Bit

<input type="checkbox"/>	310.19	100 mm, quick coupling	
--------------------------	--------	------------------------	---

### Distal Radius Fixators, sterile

#### With Self-Drilling Schanz Screws (stainless steel) and Carbon Fiber Rod

<input type="checkbox"/>	03.390.052S	200 mm Carbon Fiber Rod
<input type="checkbox"/>	03.390.053S	220 mm Carbon Fiber Rod
<input type="checkbox"/>	03.390.054S	240 mm Carbon Fiber Rod



#### With Titanium Self-Drilling Schanz Screws and Carbon Fiber Rod

<input type="checkbox"/>	03.390.055S	200 mm Carbon Fiber Rod
<input type="checkbox"/>	03.390.056S	220 mm Carbon Fiber Rod
<input type="checkbox"/>	03.390.057S	240 mm Carbon Fiber Rod