

# Inventory Control Form

## LCP Dynamic Helical Hip System (DHHS)



Patient Information:

SYNTHES (USA) To Order: (800) 523-0322	SYNTHES (Canada) Ltd. To Order: (800) 668-1119
---	---

Date: \_\_\_\_\_

Hospital: \_\_\_\_\_

Surgeon: \_\_\_\_\_

Procedure: \_\_\_\_\_

### Implants

#### LCP DHHS Compression Screw<sup>◇</sup>

211.890



#### LCP DHHS Enhanced Compression Screw, sterile

02.224.030S



#### 3.5 mm Locking Screws, self-tapping

	LENGTH
<input type="checkbox"/>	212.104 16 mm
<input type="checkbox"/>	212.106 20 mm
<input type="checkbox"/>	212.108 24 mm



#### 4.5 mm Cortex Screws, self-tapping

	LENGTH		LENGTH
<input type="checkbox"/>	214.828 28 mm	<input type="checkbox"/>	214.842 42 mm
<input type="checkbox"/>	214.830 30 mm	<input type="checkbox"/>	214.844 44 mm
<input type="checkbox"/>	214.832 32 mm	<input type="checkbox"/>	214.846 46 mm
<input type="checkbox"/>	214.834 34 mm	<input type="checkbox"/>	214.848 48 mm
<input type="checkbox"/>	214.836 36 mm	<input type="checkbox"/>	214.850 50 mm
<input type="checkbox"/>	214.838 38 mm	<input type="checkbox"/>	214.852 52 mm
<input type="checkbox"/>	214.840 40 mm	<input type="checkbox"/>	214.854 54 mm



#### 5.0 mm Locking Screws, self-tapping, with T25 StarDrive recess

	LENGTH		LENGTH
<input type="checkbox"/>	212.201 14 mm	<input type="checkbox"/>	212.212 36 mm
<input type="checkbox"/>	212.202 16 mm	<input type="checkbox"/>	212.213 38 mm
<input type="checkbox"/>	212.203 18 mm	<input type="checkbox"/>	212.214 40 mm
<input type="checkbox"/>	212.204 20 mm	<input type="checkbox"/>	212.215 42 mm
<input type="checkbox"/>	212.205 22 mm	<input type="checkbox"/>	212.216 44 mm
<input type="checkbox"/>	212.206 24 mm	<input type="checkbox"/>	212.217 46 mm
<input type="checkbox"/>	212.207 26 mm	<input type="checkbox"/>	212.218 48 mm
<input type="checkbox"/>	212.208 28 mm	<input type="checkbox"/>	212.219 50 mm
<input type="checkbox"/>	212.209 30 mm	<input type="checkbox"/>	212.220 55 mm
<input type="checkbox"/>	212.210 32 mm	<input type="checkbox"/>	212.221 60 mm
<input type="checkbox"/>	212.211 34 mm		



#### LCP DHHS Sideplates, standard barrel<sup>◇</sup>



		HOLES	ANGLE			HOLES	ANGLE
<input type="checkbox"/>	282.600	2	130°	<input type="checkbox"/>	282.605S	8	130°
<input type="checkbox"/>	282.601	3	130°	<input type="checkbox"/>	282.606S	10	130°
<input type="checkbox"/>	282.602	4	130°	<input type="checkbox"/>	282.607S	12	130°
<input type="checkbox"/>	282.603	5	130°	<input type="checkbox"/>	282.608S	14	130°
<input type="checkbox"/>	282.604	6	130°				
<input type="checkbox"/>	282.610	2	135°	<input type="checkbox"/>	282.616S	10	135°
<input type="checkbox"/>	282.611	3	135°	<input type="checkbox"/>	282.617S	12	135°
<input type="checkbox"/>	282.612	4	135°	<input type="checkbox"/>	282.618S	14	135°
<input type="checkbox"/>	282.613	5	135°	<input type="checkbox"/>	282.619S	16	135°
<input type="checkbox"/>	282.614	6	135°	<input type="checkbox"/>	282.620S	18	135°
<input type="checkbox"/>	282.615S	8	135°	<input type="checkbox"/>	282.621S	20	135°
<input type="checkbox"/>	282.630	2	140°	<input type="checkbox"/>	282.635S	8	140°
<input type="checkbox"/>	282.631	3	140°	<input type="checkbox"/>	282.636S	10	140°
<input type="checkbox"/>	282.632	4	140°	<input type="checkbox"/>	282.637S	12	140°
<input type="checkbox"/>	282.633	5	140°	<input type="checkbox"/>	282.638S	14	140°
<input type="checkbox"/>	282.634	6	140°	<input type="checkbox"/>	282.639S	16	140°
<input type="checkbox"/>	282.640	2	145°	<input type="checkbox"/>	282.645S	8	145°
<input type="checkbox"/>	282.641	3	145°	<input type="checkbox"/>	282.646S	10	145°
<input type="checkbox"/>	282.642	4	145°	<input type="checkbox"/>	282.647S	12	145°
<input type="checkbox"/>	282.643	5	145°	<input type="checkbox"/>	282.648S	14	145°
<input type="checkbox"/>	282.644	6	145°	<input type="checkbox"/>	282.649S	16	145°
<input type="checkbox"/>	282.650	2	150°	<input type="checkbox"/>	282.656S	10	150°
<input type="checkbox"/>	282.651	3	150°	<input type="checkbox"/>	282.657S	12	150°
<input type="checkbox"/>	282.652	4	150°	<input type="checkbox"/>	282.658S	14	150°
<input type="checkbox"/>	282.653	5	150°	<input type="checkbox"/>	282.659S	16	150°
<input type="checkbox"/>	282.654	6	150°	<input type="checkbox"/>	282.660S	18	150°
<input type="checkbox"/>	282.655S	8	150°	<input type="checkbox"/>	282.661S	20	150°

<sup>◇</sup>These implants are available nonsterile or sterile-packed. Add "S" to catalog number for sterile product. Item numbers ending with "S" are available sterile only.

### Implants (cont'd)


#### LCP DHHS Sideplates, short barrel<sup>◇</sup>



		HOLES	ANGLE		HOLES	ANGLE	
<input type="checkbox"/>	282.670	2	130°	<input type="checkbox"/>	282.673S	5	130°
<input type="checkbox"/>	282.671S	3	130°	<input type="checkbox"/>	282.674S	6	130°
<input type="checkbox"/>	282.672	4	130°				
<input type="checkbox"/>	282.676	2	135°	<input type="checkbox"/>	282.679S	5	135°
<input type="checkbox"/>	282.677S	3	135°	<input type="checkbox"/>	282.680S	6	135°
<input type="checkbox"/>	282.678	4	135°				
<input type="checkbox"/>	282.681S	2	140°	<input type="checkbox"/>	282.684S	5	140°
<input type="checkbox"/>	282.682S	3	140°	<input type="checkbox"/>	282.685S	6	140°
<input type="checkbox"/>	282.683	4	140°				
<input type="checkbox"/>	282.686S	2	145°	<input type="checkbox"/>	282.689S	5	145°
<input type="checkbox"/>	282.687S	3	145°	<input type="checkbox"/>	282.690S	6	145°
<input type="checkbox"/>	282.688	4	145°				
<input type="checkbox"/>	282.691	2	150°	<input type="checkbox"/>	282.694S	5	150°
<input type="checkbox"/>	282.692S	3	150°	<input type="checkbox"/>	282.695S	6	150°
<input type="checkbox"/>	282.693	4	150°				

#### Universal Locking Trochanter Stabilization Plate<sup>◇</sup>

	LENGTH
<input type="checkbox"/>	02.102.001 131 mm



#### Helix Blades<sup>◇</sup>



	LENGTH		LENGTH
<input type="checkbox"/>	282.234 75 mm	<input type="checkbox"/>	282.242 115 mm
<input type="checkbox"/>	282.235 80 mm	<input type="checkbox"/>	282.243 120 mm
<input type="checkbox"/>	282.236 85 mm	<input type="checkbox"/>	282.244 125 mm
<input type="checkbox"/>	282.237 90 mm	<input type="checkbox"/>	282.245 130 mm
<input type="checkbox"/>	282.238 95 mm	<input type="checkbox"/>	282.246S 135 mm
<input type="checkbox"/>	282.239 100 mm	<input type="checkbox"/>	282.247S 140 mm
<input type="checkbox"/>	282.240 105 mm	<input type="checkbox"/>	282.248S 145 mm
<input type="checkbox"/>	282.241 110 mm	<input type="checkbox"/>	282.249S 150 mm

### Instruments

#### Drill Bits, quick coupling



		DIAMETER	LENGTH
<input type="checkbox"/>	310.31	3.2 mm	145 mm
<input type="checkbox"/>	310.431	4.3 mm	180 mm
<input type="checkbox"/>	310.44	4.5 mm	145 mm

#### Drill Bit, 100 mm calibrated

	DIAMETER	LENGTH
<input type="checkbox"/>	324.214 2.8 mm	200 mm

#### Tap for 4.5 mm Cortex and 4.5 mm Shaft Screws



<input type="checkbox"/>	311.46	130 mm, 57 mm tap depth
--------------------------	--------	-------------------------

#### 2.5 mm Threaded Guide Wire

<input type="checkbox"/>	900.723	spade point, 230 mm
--------------------------	---------	---------------------

<sup>◇</sup>These implants are available nonsterile or sterile-packed. Add "S" to catalog number for sterile product. Item numbers ending with "S" are available sterile only.